

AD-A171 148


MINIMUM POINTS AND VIEWS FOR THE RECOVERY OF
THREE-DIMENSIONAL STRUCTURE(U) CALIFORNIA UNIV IRVINE
COGNITIVE SCIENCES GROUP M L BRAUNSTEIN ET AL.
20 JUN 86 N00014-85-K-0529


1/1

UNCLASSIFIED

F/G 6/16

NL





MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

AD-A171 148

Studies in the Cognitive Sciences

-41-

Minimum Points and Views for the Recovery
of Three-Dimensional Structure

Myron L. Braunstein
Donald D. Hoffman
Lionel R. Shapiro
George J. Andersen
Bruce M. Bennett

N00014-85-K-0529
NR 196-194

This document has been approved
for public release and sale; its
distribution is unlimited.



DTIC
ELECTE
AUG 22 1986

University of California, Irvine

School of Social Sciences

Reproduction in whole or in part is permitted for
any purpose of the United States Government.

86 8 22 07 8

DTIC FILE COPY

N00014-85-K-0529

NR 196-194

**Minimum Points and Views for the Recovery
of Three-Dimensional Structure**

Myron L. Braunstein

Donald D. Hoffman

Lionel R. Shapiro

George J. Andersen

Bruce M. Bennett

Studies in the Cognitive Sciences, 41

July, 1986

**School of Social Sciences
University of California, Irvine
Irvine, California, 92717**

**DTIC
ELECTE
AUG 22 1986
A**

This document has been approved
for public release and sale; its
distribution is unlimited.

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Minimum points and views for the recovery of three-dimensional structure		5. TYPE OF REPORT & PERIOD COVERED Technical
		6. PERFORMING ORG. REPORT NUMBER 41
7. AUTHOR(s) Myron L. Braunstein, Donald D. Hoffman, Lionel R. Shapiro, George J. Andersen, Bruce M. Bennett		8. CONTRACT OR GRANT NUMBER(s) N00014-85-K-0529
9. PERFORMING ORGANIZATION NAME AND ADDRESS Cognitive Sciences Group, School of Social Sci. University of California, Irvine Irvine, CA 92717		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS NR 196-194
11. CONTROLLING OFFICE NAME AND ADDRESS Office of Naval Research Engineering Psychology Program (Code 1142EP) Arlington, VA 22217-5000		12. REPORT DATE 20 June 1986
		13. NUMBER OF PAGES
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		15. SECURITY CLASS. (of this report)
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number)		
<div style="display: flex; justify-content: space-between;"> <div> depth velocity structure orthographic </div> <div> motion fixed-axis grouping rotation </div> <div> images constraints three-dimensional </div> </div>		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number)		
<p>→ Mathematical analyses of motion perception have established minimum combinations of points and distinct views that are sufficient to recover three-dimensional (3D) structure from two-dimensional (2D) images, using such regularities as rigid motion, fixed axis of rotation, and constant angular velocity. To determine whether human subjects could recover 3D information at these theoretical levels, we presented subjects with pairs of displays and asked them to determine whether they</p>		

20. (continued)

represented the same or different 3D structures. Number of points was varied between 2 and 5; number of views was varied between 2 and 6; and the motion was either fixed axis with constant angular velocity, fixed axis with variable velocity, or variable axis with variable velocity. Accuracy increased with views, but decreased with points, apparently due to the increased difficulty of the comparison task as the structure became more complex. Subjects' performance exceeded theoretical expectations, implying that they exploited regularities in addition to those in the theoretical analyses. Some possible additional regularities, and possible grouping effects, are discussed.

Table of Contents

Abstract	ii
Acknowledgments	ii
1. Introduction	1
2. Method	
2.1 Subjects	4
2.2 Design	5
2.3 Stimuli	5
2.4 Apparatus	7
2.5 Procedure	7
3. Results	8
4. Discussion	15
References	20
Appendix A: Response data, d'	22
Appendix B: Response latency data	23



Accession For	
NTIC - NSA&I	<input checked="checked" type="checkbox"/>
NTIC - TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By _____	
Distribution/	
Availability Codes	
Avail and/or	
Special	

A-1

Abstract

Mathematical analyses of motion perception have established minimum combinations of points and distinct views that are sufficient to recover three-dimensional (3D) structure from two-dimensional (2D) images, using such regularities as rigid motion, fixed axis of rotation, and constant angular velocity. To determine whether human subjects could recover 3D information at these theoretical levels, we presented subjects with pairs of displays and asked them to determine whether they represented the same or different 3D structures. Number of points was varied between 2 and 5; number of views was varied between 2 and 6; and the motion was either fixed axis with constant angular velocity, fixed axis with variable velocity, or variable axis with variable velocity. Accuracy increased with views, but decreased with points, apparently due to the increased difficulty of the comparison task as the structure became more complex. Subjects' performance exceeded theoretical expectations, implying that they exploited regularities in addition to those in the theoretical analyses. Some possible additional regularities, and possible grouping effects, are discussed.

Acknowledgments

This research was supported by a contract to D. Hoffman from the Office of Naval Research, Cognitive and Neural Sciences Division, Perceptual Sciences Group. We thank Johnna Eastburn for assistance in various aspects of this research.

1. Introduction

Theoretical investigations of visual motion have provided a number of specific analyses of the minimum number of points and views required to recover three-dimensional (3D) structure from two-dimensional (2D) images. Recovery of 3D structure, in this context, is defined as determining the x, y, and z coordinate of each point, up to a scale factor. These analyses differ in the constraints that are imposed. Ullman (1979) showed that under a rigidity constraint, three views of four noncoplanar points are sufficient to recover structure in an orthographic projection, up to a reflection about the frontal plane. The required numbers of points and views are reduced by adding further constraints, such as planarity (Hoffman & Flinchbaugh, 1982), fixed axis of rotation (Hoffman & Bennett, 1986; Webb & Aggarwal, 1981), and constant angular velocity (Hoffman & Bennett, 1985). These proofs are summarized in Table 1.

Table 1
Sufficient Conditions for the Recovery of 3D Structure

		Number of Points		
		2	3	4
Number of Distinct Views	2		Pairwise-rigid and planar motion ^a	
	3	Rigid planar motion ^a Rigid fixed axis motion parallel to image plane, constant angular velocity ^b	Rigid fixed axis motion ^b	Rigid motion ^c Nonrigid fixed axis motion ^d
	4	Nonrigid fixed axis motion ^d Rigid fixed axis motion, constant angular velocity ^c		
	5	Rigid fixed axis motion ^c		

^aHoffman & Flinchbaugh, 1982; ^bHoffman & Bennett, 1986; ^cUllman, 1979; ^dBennett & Hoffman, 1985; ^eHoffman & Bennett, 1985

A number of empirical studies have addressed issues related to theoretical analyses of the recovery of structure from motion. Several studies (for example, Braunstein & Andersen, 1985; Schwartz & Sperling, 1983; Todd, 1985) have questioned the generality of the rigidity constraint. Other studies have considered the recovery of structure with small numbers of views or with small numbers of points. Lappin, Doner, & Kottas (1980) found that subjects could make accurate judgments based on 3D structure with two perspective views of 512 points. Lappin and Fuqua (1983) found a high level of accuracy for relative depth judgments with 120° rotations of three-point configurations. There have not been studies, however, of the recovery of structure from motion using the minimum combinations of points and views found in the theoretical analyses discussed above.

There are several reasons why these theoretical analyses should be considered empirically. First, it is worthwhile to determine whether the performance of human observers approaches the performance of the "ideal" observers in these analyses. Can the human observer recover 3D structure at the minimum combinations of points and views? Second, it is useful to know whether performance improves as predicted by these theoretical analyses when constraints, in addition to rigidity, are imposed on the displays. Specifically, can structure be recovered with fewer points and views when the axis of rotation is fixed and when a constant angular velocity is maintained across views? Third, empirical studies may suggest other constraints used by human observers that have not been considered in theoretical analyses.

On the negative side, one can question the ecological validity of minimum information displays, and of orthographic projections in particular. These displays are clearly special cases. Visual perception normally occurs in richly textured environments with continuous observation. Orthographic projection simulates an infinite viewing distance, eliminating the perspective effects found in normal vision. With these considerations in mind, we still believe that these displays provide a useful starting point for bringing together specific mathematical analyses with psychophysical procedures.

There are at least two fundamental difficulties in applying a psychophysical approach to the testing of theoretical analyses of the recovery of structure from motion. The first stems from the definition given above, according to which recovery of structure consists of determining coordinates in 3D space. This definition provides a suitable measure for computer simulations, but it is not reasonable to expect a human subject to call out coordinates while observing a group of points undergoing a rotation. Some dependent variable is needed, one that is

logically related to the recovery of structure but that is based on a reasonable human response. This will be discussed further in the following paragraphs.

The second difficulty is inherent in the task--recovering 3D structure from 2D images. The information for the recovery of the structure must be available in the images, and therefore any task given the subject to determine whether the structure has been recovered must be possible on the basis of the images. How, then, do we know that the subject is not performing the task on the basis of some 2D characteristic of the images without recovering the 3D structure? There is no way, in principle, to be certain of this. As discussed below, the best we can do is to try to find and eliminate any 2D regularities that a subject could use to perform the task without also recovering the 3D structure.

In the first task that we used in pilot studies, displays were generated consisting of three, four or eight points that were the vertices of regular polygons. Each display was paired with a polygon in which the location of one of the vertices relative to the others was altered by a controlled amount, so that the polygon was no longer regular. The subjects viewed the displays side by side. To prevent direct image comparisons, the two polygons were never displayed in the same orientation. Several experienced subjects reported noticeable regularities in the 2D images of the regular polygons, regularities that made it possible for them to distinguish between the regular and irregular polygons in each pair. Although all of these apparent regularities could not be described precisely by the subjects, they appeared to be related to the use of regular polygons as the standard stimuli, and we therefore abandoned that approach.

Instead, we used displays consisting of sets of points that were randomly generated (under restrictions described in the Method section). For each display, a comparison display was presented that was identical to the standard or had one point moved to a different position. The subject's task was to indicate whether the 3D structures represented by the two displays were the same or different. The rationale for using a comparison task as a measure of recovery of structure is that subjects must recover the 3D structure in order to determine whether the displays represent the same or different configurations. Although the task can be performed by comparing substructures if the number of points exceeds the minimum required, it should be necessary to use all of the points to recover the 3D structure of a configuration at the minimum levels.

For the reasons stated above, the two displays were presented out of phase. This probably required the subject to mentally rotate one or both structures to

compare them. This extra step of mental rotation, between recovery of the structures and the behavioral response, could have prevented subjects from responding accurately (above chance) to the combinations of small numbers of points and small numbers of views listed in Table 1. As we will indicate below, this did not seem to be the case in our experiment.

Each of the mathematical analyses in Table 1 gives sufficiency conditions for recovering the third dimension if one assumes some specific regularity or regularities in the motion of the simulated object. The individual analyses do not make predictions about improvements in performance with increasing numbers of points or views, or with further constraints. If all of these analyses were instantiated in the visual system, however, we would expect the following results for the numbers of points and views and the motion constraints included in the present experiment:

- (1) Accuracy should increase with the number of distinct views.
- (2) Accuracy should increase with the number of points.
- (3) Accuracy should increase with increasing constraints, from variable axis to fixed axis to fixed axis with constant angular velocity.

In addition to these general trends, accuracy should increase from chance to above chance at the critical combinations of points, views, and constraints listed in Table 1: (a) four points, three views, no added constraints (rigidity only); (b) three points, three views, rigidity and fixed axis constraints; (c) two points, five views, rigidity and fixed axis constraints; and (d) two points, four views, rigidity, fixed axis, and constant angular velocity.

2. Method

2.1 Subjects

The subjects were five graduate students and one undergraduate from the School of Social Sciences at the University of California, Irvine. Subjects were paid for their participation. One subject (No. 1), had been directly involved in the research, two were slightly acquainted with the research (Nos. 2 and 3), and three were naive. Acuity of at least 20/40 (Snellen eye chart) was required in the eye the subject used throughout the course of the experiment. Each subject met a performance criterion of 75% or better (overall correct on the *same/different* judgments) during a screening session consisting of 200 trials with 30 views, 3-5 points, and fixed axis/constant angular velocity. Two of the subjects (Nos. 5 and 6), both naive, were run without feedback. The remaining subjects were run with feedback on all trials.




Figure 1. Experimental design.

2.2 Design

We examined three independent variables: number of points in a simulated object, number of distinct views presented, and motion constraints (see Figure 1). The number of points in a simulated object ranged from two to five. The number of distinct views presented ranged from two to six. The motion conditions examined were: (a) fixed axis of rotation with constant angular velocity, (b) fixed axis of rotation with a variable angular velocity, and (c) variable axis of rotation. All of the independent variables were run within subjects. Each subject responded to 50 trials of each of the 60 stimulus conditions. Each subject also responded to 75 30-view "baseline" trials at each combination of number of points and motion condition.

2.3 Stimuli

A stimulus consisted of two to five light green dots, changing in position, against a dark green background. Each stimulus simulated points on a rigid object rotating in depth. Preliminary point positions for an object were selected at random (without replacement) from a uniform distribution of 225 potential point positions on the surface of a unit-radius sphere. To avoid any unintended regularities in the projection that might have resulted from all points being equidistant from the center of rotation, the distance of each point to the center of the sphere was randomly perturbed within a range of ± 0.2 units. This configuration of points was defined as the standard object. For *same* trials, the comparison object was identical to the standard object. For *different* trials, the following method was used to generate the comparison object: One of the points on the standard object was moved to one of the 225 potential point positions that was unoccupied. The point to be moved and the new position were selected at random. If the root mean square (RMS) of the

changes in distance (standard object distance minus comparison object distance) from the moved point to all other points in the simulated object did not exceed 0.7 units, these simulated objects were discarded and a new standard was generated. The minimum RMS distance criterion was determined, through pilot studies, to provide a better than 0.8 overall proportion correct for an experienced subject in fixed axis/constant angular velocity displays. As a result of this criterion, and the restrictions described below, the RMS difference varied between 0.7 and 1.88, with a mean of 0.90 and a standard deviation of 0.30.

In order to avoid the possibility of subjects making direct comparisons of the 2D projections, the two simulated objects were set at different initial orientations: 20° slant, 0° tilt for the standard and 50° slant, 0° tilt for the comparison object. (See Stevens, 1983, for a discussion of slant and tilt.) In addition, the standard and comparison objects were always out of phase, with their initial phase difference randomly varied within a range of 40° to 140°.

Each stimulus display consisted of a sequence of distinct, orthogonal views of a simulated object undergoing a specific type of motion in three dimensions. In order to allow subjects sufficient time to observe the displays and make a judgment, the sequence of views was oscillated (e.g., 1, 2, ... n-1, n, n-1, ... 2, 1, 2, ...) at a rate of 16 views per sec until the subject responded. (If the subject did not respond within 60 sec, the trial was repeated at the end of the session.) For the fixed axis conditions, these views were rotations from the initial orientation about an axis at 20° slant, 0° tilt for the standard and 50° slant, 0° tilt for the comparison object. For constant angular velocity conditions, the rotation between successive views was 6°.

The variability in angular velocity in the variable velocity condition and the variability in axis of rotation in the variable axis condition could not be unrestricted. Otherwise, difficulty in maintaining the identity of points from frame to frame (correspondence matches) and in perceiving smooth motion might have confounded the effects of variability. These two factors were controlled first by limiting the variance of the distribution from which the velocities and axis shifts were sampled and then by imposing a correspondence match criterion and a 2D motion criterion (described below) on each display. The mean axis change and mean velocity change in the variable axis and variable velocity conditions was set equal to the axis and velocity changes between views in the fixed axis and velocity conditions. To induce variability within a restricted range, the axis shifts between views in the variable axis condition and the angular rotations between views in the variable

velocity condition were sampled from a distribution consisting of the sum of two bimodal distributions. The means of the two distributions were 2° and 10° , respectively. Each distribution had a standard deviation of 0.71 and modes at ± 0.7 standard deviations from its mean. A minimum variance criterion for axis shift or angular rotation was used to control for chance selection of nearly equal axis or rotation values across views in the variable axis or variable velocity conditions.

Displays were used only if the following two restrictions were satisfied: In order to reduce the possibility of false correspondence matches of points across pairs of views, the nearest neighbor to any given point, from one view to the next, had to be the correctly corresponding point. This restriction was not applied to points with opposite depth signs, which would be moving in opposite directions. In order to maintain conditions for "short-range" apparent motion across pairs of views, the distance moved by any given point in the image was not allowed to exceed $15'$ of visual angle (Braddick, 1974).

2.4 Apparatus

The stimuli were presented on a Hewlett-Packard Model 1321B X-Y Display with a P-31 phosphor, under the control of a PDP 11/44 computer. The subject viewed the display through a tube arrangement that limited the field of view to a circular area 7.6° in diam. The maximum projected diameter of each simulated object occupied 840 plotting positions on the CRT and subtended a visual angle of 2.1° . The center to center separation of the objects was 3.8° . The eye to screen distance was 1.71 m. The dot and background brightnesses at the screen were approximately 5 cd/m^2 and 0.002 cd/m^2 , respectively. A 0.5 neutral-density filter was inserted in the viewing tube to remove any apparent traces on the CRT.

Three models constructed from metal and plastic were used to instruct the subjects. Each model consisted of four white spheres connected by black rods. Two of the models were identical. The third model differed from the others only in the position of one of its spheres. The subjects responded by pressing one of two switches labeled *same* and *different*, respectively. The responses and response latencies were recorded by the PDP 11/44.

2.5 Procedure

Subjects were instructed to make *same* or *different* judgments for pairs of stimuli based upon the following criterion: "The two groups are the same when all of the distances between the dots are the same, regardless of their orientation. The two groups of dots are different when the distances between at least two of the dots are different." The three models were used to demonstrate the judgment criterion.

Subjects who were to receive feedback were told that a single tone would indicate a correct response and that two successive tones would indicate an incorrect response. The room was darkened 2 min before the trials began.

Each subject participated in an initial screening session, 25 experimental sessions, and a follow-up session with debriefing. After the first session, subjects initiated each session individually. Each experimental session consisted of three blocks: a baseline monitoring block and two experimental blocks. The baseline monitoring block consisted of three trials of 30 views at each combination of levels of the points and motion variables, in a random order. These trials were used to assure that the subjects maintained a high level of accuracy when the number of views far exceeds the expected minimum levels. The 30-view trials were also intended to assure that any failure to respond accurately at the minimum view levels was not due to the mental rotation component of the task, which should have been the same on the 30-view trials. Each experimental block consisted of 60 trials, each selected at random from the 60 possible conditions. There was a 2 min rest period between each block of trials.

3. Results

The subject's task may be interpreted as determining whether or not there was a difference between the 3D structures represented by the standard and comparison stimuli. A signal detection paradigm (Green & Swets, 1966) was used to analyze the results, with the *different* trials serving as signal trials. A d' measure was computed for each subject and stimulus condition, using the proportion of *different* responses on *different* trials as the hit rate and the proportion of *different* responses on *same* trials as the false alarm rate. Each d' was based on 50 trials, approximately half of which were signal (*different*) trials (see Appendix A for d' scores).

An analysis of variance revealed significant main effects for number of points, $F(3, 15) = 14.99$, $p < .01$, and number of distinct views, $F(4, 20) = 28.91$, $p < .01$. As shown in Figure 2, d' decreased with increasing numbers of points. This is opposite to the result that would be expected if the theoretical analyses in Table 1 were used to recover the 3D structures from the 2D images. This unexpected result is probably due to differences between the idealized process of recovery of structure and the requirements of the comparison task used in the present experiment. These differences will be discussed below.




Figure 2. Effect of number of points on d' for 2-6 views. (Data points for individual subjects are based on 750 observations.)




Figure 3. Effect of number of distinct views on d' . (Data points for individual subjects are based on 600 observations.)

As expected, d' increased with increasing number of views (see Figure 3). The main effect of motion constraint was not significant, $F(2, 10) = 3.12$, $p > .05$, but there was a significant interaction of motion constraint with points, $F(6, 30) = 4.74$, $p < .01$, and a second order interaction of motion constraint with points and views, $F(24, 120) = 3.51$, $p < .01$. The motion/points interaction, illustrated in Figure 4, shows a sharper drop in accuracy after three points in the variable axis condition than in the other two motion conditions. Separate inspection of the proportions of correct responses for the *same* and *different* trials (Figure 5) indicates that this interaction, as well as the main effect of points, was primarily due




Figure 4. Interaction of number of points with motion condition for 2-6 views.




Figure 5. Interaction of number of points with motion condition for *same* and *different* trials.

to the *same* trials. There was also a significant interaction of number of points with number of distinct views, $F(12, 60) = 2.78$, $p < .01$ (see Figure 6). The magnitudes of the significant effects, ω^2 , for points, views, points by views by motion constraint, points by views, and points by motion constraint, were .172, .099, .072, .025, and .018 respectively. The main effects of motion constraint, $F(2, 10) = 3.12$, and the interaction of motion constraint with views, $F(8, 40) = 1.31$, were not significant, $p > .05$.




Figure 6. Interaction of number of points with number of distinct views.




Figure 7. Interaction of number of points, number of distinct views, and motion condition.

A second order interaction would be expected if different combinations of points and views are required to recover structure under different motion constraints. Although a significant second order interaction occurred (Figure 7), there is no indication that this interaction was related to the critical combinations of points, views, and motion constraints listed in Table 1. The significance of the d' scores was calculated for each subject and points/views/motion combination using Marascuilo's one signal significance test (1970, pp. 238-240). In general, d' decreased as expected when the number of views dropped below the levels required in the critical combinations, but d' did not drop to chance as soon as the number of views dropped below the number theoretically required to recover structure, for a given combination of points and motion constraints. On the other hand, d' generally increased as the number of points was reduced which, as noted above, is not consistent with the theoretical analyses of recovery of structure. Of the 360 d' scores, 351 were significantly different from zero, $p < .05$ (see also Appendix A). For three subjects, d' dropped to chance levels when the fixed axis constraint was removed for five points and two distinct views. (This is not one of the critical combinations, however.) There was no systematic pattern to the remaining




Figure 8. Effect of number of points on d' for 30 views. (Data points for individual subjects are based on 1125 observations).




Figure 9. Interaction of number of points with motion condition for 30 views.




Figure 10. Interaction of number of points with motion condition for *same* and *different*, 30 view trials.




Figure 11. Interaction of number of points with number of distinct views for β .

nonsignificant d 's, except that half of these were due to one of the subjects (No. 5). Overall, the critical combinations presented in Table 1 do not seem to be relevant to human performance in the comparison task used in this experiment.

Significant d 's were found for all subjects in the two-point/two-view conditions, for all three motion conditions. This is a remarkable finding as that combination of points and views falls below the minimum required to recover 3D structure under the constraints used in existing structure-from-motion proofs. The possibility that subjects exploited additional constraints in the present experiment will be discussed below.

A separate analysis was conducted for the d' measure for 30-view trials. The main effect of number of points was significant, $F(3, 15) = 19.92$, $p < .01$, $\omega^2 = .311$ (see Figure 8). The d' values for two, three, four, and five points were 3.21, 3.18, 2.64, and 2.20, respectively. The interaction of motion condition with points was also significant, $F(6, 30) = 2.81$, $p < .05$, $\omega^2 = .052$ (see Figure 9). This interaction was generally similar to that found for the 2-6 view conditions, although, as seen in Figure 10, the reduction in accuracy with increasing number of points seems to be due primarily to *different* trials. The main effect of motion condition was not significant, $F(2, 10) < 1$.

An analysis of variance of the subjects' response biases, β , for all subjects and conditions revealed significant effects only for number of distinct views, $F(4, 20) = 4.25$, $p < .05$, and for the interaction of number of points with number of views, $F(12, 60) = 2.33$, $p < .05$. (The ω^2 values for these two

effects were .019 and .037, respectively.) As the number of views increased, subjects' bias changed from no bias to a *different* response bias. This bias was most noticeable for five or six views of two or three points (see Figure 11).

An analysis of variance was conducted for the mean response latencies (see Appendix B) for the 2-6 view conditions. An additional independent variable, trial type (*same* or *different*) was used in this analysis. (This variable does not appear in the d' analysis because both types of trials were used in computing d' .) The number of points accounted for most of the variance, $F(3, 15) = 47.1$, $p < .01$, $\omega^2 = .657$. The mean latencies for 2-5 point displays were 3.60, 4.86, 8.08, and 10.58 sec, respectively. There were no other significant main effects. There were four significant interactions: points with motion, $F(6, 30) = 3.24$, $p < .05$; points with views with motion, $F(24, 120) = 2.42$, $p < .01$; trial type with views, $F(4, 20) = 7.62$, $p < .01$; and points with type with views, $F(12, 60) = 2.29$, $p < .05$. All of these interactions were relatively small; the ω^2 values for the four interactions were .015, .032, .052, and .016, respectively. If subjects compared all interpoint distances across displays on *same* trials, but responded as soon as one nonmatching distance was found on *different* trials, there should have been an interaction of number of points with type of trial. This interaction was not significant, $F(3, 15) = 1.14$, $\omega^2 = .0013$. A comparison of these values to the large main effect found for number of points indicates that this type of differential processing of *same* and *different* trials did not occur.

In response to debriefing questions, all but one of the subjects reported seeing the simulated objects as 3D on 80-100% of the trials. One subject, No. 5, reported only 2D interpretations for the first 12 sessions and 3D interpretations on 90% of the trials in the latter 13 sessions. Figures 1 and 2 show the d 's for this subject to be consistently below those of the other five subjects.

4. Discussion

Theoretical analyses of the recovery of 3D structure from 2D images have shown that three views of four points are sufficient to recover structure under a rigidity constraint (Ullman, 1979), with fewer points required as additional constraints and/or views are added (Hoffman & Bennett, 1985; 1986). As these proofs assume infinitely fine resolution and the absence of noise, one might expect poorer performance by the human observer. More views should be required if an incremental rigidity scheme (Ullman, 1984) were used to overcome the effects of noise. Human performance in our experiment might be expected to be degraded

further because of the interposition of a task possibly requiring mental rotation between the recovery of structure and the behavioral response. For these reasons, our finding that subjects could make accurate psychophysical judgments with fewer points and distinct views than expected on the basis of theoretical analyses is especially surprising. It should of course be emphasized that the theoretical analyses are concerned with recovery of the 3D coordinates of points in an arbitrarily-scaled space, up to a reflection about the image plane, whereas our subjects were comparing pairs of structures. The implications of these differences between the theoretical concept of recovery of structure and the requirements of our behavioral task will be discussed below. Still, it is remarkable that any task in which subjects were required to respond to 3D relationships based on information in dynamic monocular displays could be performed on the basis of as few as two points and two distinct views.

Subjects should not have been able to perform significantly above chance with two points and two distinct views if the only constraint incorporated in their processing of the image data was rigidity, or even if fixed axis and constant angular velocity constraints were applied. This suggests that subjects exploited additional constraints that are not included in the theoretical analyses. In a mathematical analysis, it is possible to specify a limited set of applicable constraints, such as rigidity, fixed axis of rotation, and constant angular velocity. In presenting displays to human subjects, however, additional constraints may become applicable. First, the subjects may exploit the constraint of a constant relationship, across displays, between the distances in the projection and the 3D distances that are represented. Scale is undetermined in the mathematical analyses, and the subjects indeed may impose an arbitrary scale in recovering the 3D structures of the displays. It seems unlikely that different scales would be imposed on different displays, however, especially for displays within the same pair. The assumption that the scale is the same for both displays in a pair is essential to accurate responding to the two-point displays. Indeed, we could not have scored a *same* or *different* response to a pair of two-point displays as correct or incorrect without assuming equal scales.

Second, in the mathematical analyses discussed above, rigid translations of the configuration of points do not provide information about the structure. It is assumed, for example, that the subject fixates one point. (Eye movements required to maintain this fixation are not considered as sources of information for use in recovering the structure.) In our experiment, the subjects may have used the lack of translation of the center of rotation as an additional constraint. (To match the

theoretical analyses, it would be necessary to link the image to movements of the subject's eye so that one point was always fixated, but no eye movements were required to maintain the fixation.)

Third, in the variable velocity and variable axis conditions, subjects may have exploited the constraint that these variations occurred within a limited range. These limitations were necessary to meet other requirements of structure-from-motion analyses. These analyses are applicable only if the correspondence of points from frame to frame is correctly resolved. If a nearest neighbor criterion is postulated for correspondence matches, displayed points should not be moved to positions that bring them closer to the previous position of another point than to their own previous position. In general, this restricts the amount of rotation to be displayed between views. We limited our displays to distances within the short-range motion process (Braddick, 1974), further restricting the amount of rotation. These restrictions may have reduced potential differences between the three motion conditions.

Our finding of above chance performance with as few as two points and two views was not the only unexpected result. Recovery of structure, for small numbers of points and views, might be expected to be more accurate as the number of points is increased. We found, on the contrary, that accuracy decreased with increasing numbers of points. This result is probably another reflection of the differences between the theoretical operation of recovering structure and the requirements of a behavioral task. Increasing the number of points in an object may enable a subject to recover the 3D structure with fewer views or motion constraints. On the other hand, increasing the number of points increases the complexity of the structure, in terms of the number of interpoint distances. For this reason, any task used to ascertain that the relative depth coordinates of all points in the structure have been correctly recovered is likely to be more difficult for greater numbers of points. This appears to have been the case for the comparison task in the present experiment. This conclusion is supported by the latency results: Response time increased as the number of points in the structures increased.

We found that the decrease in accuracy with increasing numbers of points occurred primarily in the *same* trials. This finding is consistent with an explanation of the relationship between accuracy and the number of points based on the subject's attempting to compare interpoint distances. On a *different* trial, the subject would need only to be certain that at least one interpoint distance was not the same in both stimuli in a pair. On *same* trials, the subject would have to keep track of all of the

interpoint distances. Failure to detect any mismatch in distances could lead to an incorrect response. There was no corresponding difference in latency for *same* and *different* trials, however, suggesting that the number of comparisons required was not different for the two types of trials. There is another possible reason for higher accuracy on the *different* trials. To verify that two structures are the same, each must be recovered uniquely. To determine that two structures are different, it is only necessary to identify a set of possible structures for each display, and to determine that these two sets do not overlap.

The drop in accuracy with increasing numbers of points on *same* trials was especially marked after three points for the variable axis condition. Verbal reports indicated that the subjects attempted to organize the display into subunits of no more than three points. A four-point display might be perceived as a triangle and a dot; a five point display as a triangle and a rod. Our hypothesis is that it was more difficult to maintain a perception of rigid relationships among subunits for the variable axis displays. The use of triangular subunits by subjects in these judgments, and the importance of triangles in the analysis of optic flow (Koenderink & van Doorn, 1986), may be more than coincidental.

These suggestions of possible grouping effects indicates that organization of feature points into subgroups should be examined as a potentially important component of the recovery of 3D structure from dynamic 2D images. Some principles for grouping based on orthographic projections of rotation in depth have been reported by Gillam (1976). In studies of the recovery of structure from motion, it would be important to determine whether grouping was based on 3D or on 2D relationships. This might indicate whether grouping or recovery of structure occurred first, or perhaps would show that the two processes occur in parallel.

In summary, we have used an indirect method to test theories about the recovery of structure from motion that are not directly testable. We found that human observers could perform a structure comparison task at better than chance levels with fewer points and views than should have been necessary for the recovery of separate structures. This implies that constraints other than those considered in these theories were exploited by the subjects. Some of these possible constraints might be incorporated into theoretical analyses of the recovery of structure from minimum points and views: (a) Even when scale is undetermined, the scale used to recover structure may not be arbitrary, but may depend on assumptions of constant scale or an assumption of a specific scale. These assumptions correspond to the equidistance tendency and the specific distance tendency (Gogel, 1973).

(b) Information that specifies a fixed center of rotation, as might occur when rotation is induced by observer head movements, may be used in the recovery of structure. (c) Even when precise constant velocity and fixed axis assumptions are not applicable, most motions occur within a limited range of velocity change and axis change--that is, velocity and axis of rotation usually changes smoothly.

There remains a general lack of direct tests of mathematical theories of the recovery of structure from motion. To achieve such tests, it may be necessary to elaborate existing theories to include direct implications about human competency in tasks that are subject to psychophysical testing. It may also be necessary to develop psychophysical techniques that are more suitable for the study of dynamic information for depth perception than current techniques, which emphasize detection of minimal differences. The issue of interest in this research is often how a particular flow pattern leads to a particular perception, rather than whether an experienced observer can discriminate minimum differences in optic flow. As such developments in mathematical analysis and in psychophysics proceed, it should become possible to combine mathematical and psychophysical approaches to the study of more complex patterns of optic flow (Koenderink, 1986).

References

- Bennett, B., & Hoffman, D. (1985). The computation of structure from fixed axis motion: nonrigid structures. *Biological Cybernetics*, 51, 293-300.
- Braddick, O. (1974). A short-range process in apparent motion. *Vision Research*, 14, 519-527.
- Braunstein, M. L., & Andersen, G. J. (1985). *Testing the rigidity assumption: A reply to Ullman*. Manuscript submitted for publication.
- Gillam, B. (1976). Grouping of multiple ambiguous contours: Towards an understanding of surface perception. *Perception*, 5, 203-209.
- Gogel, W. C. (1973). The organization of perceived space: I. Perceptual interactions. *Psychologische Forschung*, 36, 195-221.
- Green, D. M., & Swets, J. A. (1966). *Signal detection theory and psychophysics*. New York: John Wiley & Sons.
- Hoffman, D., & Bennett, B. (1985). Inferring the relative 3-D positions of two moving points. *Journal of the Optical Society of America*, 75, 350-533.
- Hoffman, D., & Bennett, B. (1986). The computation of structure from fixed axis motion: rigid structures. *Biological Cybernetics*, 54, 1-13.
- Hoffman, D., & Flinchbaugh, B. (1982). The interpretation of biological motion. *Biological Cybernetics*, 42, 197-204.
- Koenderink, J. J., & van Doorn, A. J. (1986). Depth and shape from differential perspective in the presence of bending deformations. *Journal of the Optical Society of America*, 3, 242-249.
- Koenderink, J. J. (1986). Optic flow. *Vision Research*, 26, 161-180.
- Lappin, J. S., & Fuqua, M. A. (1983). Accurate visual measurement of three-dimensional moving patterns. *Science*, 221, 480-482.
- Lappin, J. S., Doner, J. F., & Kottas, B. (1980). Minimal conditions for the visual detection of structure and motion in three dimensions. *Science*, 209, 717-719.
- Marascuilo, L. A. (1970). Extensions of the significance test for one-parameter signal detection hypotheses. *Psychometrika*, 35, 237-243.
- Schwartz, B. J., & Sperling G. (1983). Nonrigid 3D percepts from 2D representations of rigid objects. *Investigative Ophthalmology and Visual Science*, 24 (3, Supplement), 239.
- Stevens, K. A. (1983). Surface tilt (the direction of slant): A neglected psychophysical variable. *Perception & Psychophysics*, 33, 241-250.

- Todd, J. (1985). The perception of structure from motion: Is projective correspondence of moving elements a necessary condition? *Journal of Experimental Psychology: Human Perception and Performance*, 11, 689-710.
- Ullman, S. (1979). *The interpretation of visual motion*. Cambridge, MA: MIT Press.
- Ullman, S. (1984). Maximizing rigidity: The incremental recovery of 3-D structure from rigid and nonrigid motion. *Perception*, 13, 255-274.
- Webb, J. A., & Aggarwal, J. K. (1981). Visually interpreting the motion of objects in space. *Computer*, 14(8), 40-46.

Response data, d' , by subject, number of distinct views, number of points, and motion condition (C = constant angular velocity, fixed axis, rigid; F = fixed axis, rigid; R = rigid). ([†]Nonsignificant scores, $p > .05$.)

22

Appendix B

Response latencies in seconds, by subject, trial type, number of distinct views, number of points, and motion condition (C = constant angular velocity, fixed axis, rigid; F = fixed axis, rigid; R = rigid).

Number of points												
2			3			4			5			
Motion condition: (v = Number of distinct views)												
v :	C	F	R	C	F	R	C	F	R	C	F	R
Subject 1												
Same trials												
30 :	4.78	4.59	5.53	5.87	5.89	6.23	7.80	6.70	7.95	9.24	10.17	12.36
2 :	3.60	4.44	4.95	6.04	5.04	5.12	6.46	8.12	7.64	12.42	9.99	10.77
3 :	3.75	3.95	3.93	5.76	6.35	6.89	10.96	9.25	8.61	11.91	13.68	11.52
4 :	4.87	4.35	4.31	6.00	6.30	4.03	8.76	9.51	7.20	9.59	9.56	12.02
5 :	3.89	4.40	4.40	4.74	6.36	5.68	9.36	8.82	10.83	12.96	12.88	11.17
6 :	4.45	4.07	3.81	4.49	4.76	4.40	9.30	8.91	7.43	13.17	12.41	11.32
Different trials												
30 :	5.38	4.26	3.67	5.16	6.16	4.84	9.01	9.23	7.34	12.46	11.09	11.08
2 :	4.14	4.70	5.03	5.45	6.60	3.97	9.27	7.20	8.40	10.40	10.52	11.52
3 :	4.51	5.74	3.10	5.95	5.48	5.93	7.17	9.39	9.48	12.70	9.53	10.96
4 :	3.97	3.98	4.80	4.97	5.99	5.08	10.46	8.38	10.59	15.09	10.75	11.61
5 :	5.11	4.54	4.75	5.72	5.21	5.45	8.42	9.15	9.26	8.64	11.68	10.90
6 :	4.58	3.64	5.01	5.05	4.70	6.70	8.70	6.60	9.88	14.12	9.18	10.66
Subject 2												
Same trials												
30 :	3.54	2.51	3.44	3.85	5.48	4.36	4.51	4.30	8.39	6.31	7.22	13.31
2 :	3.43	4.07	3.43	3.29	3.81	4.56	7.36	7.09	7.01	9.59	9.60	12.97
3 :	2.16	4.28	3.60	6.19	4.50	6.30	8.40	9.73	9.98	13.88	14.13	15.93
4 :	4.61	3.26	3.79	5.69	7.79	7.12	9.98	13.47	11.90	17.83	16.61	19.27
5 :	4.25	4.63	5.37	6.95	9.17	6.66	9.03	9.36	11.13	14.19	16.91	15.01
6 :	3.85	4.00	4.05	5.92	5.83	5.83	12.13	10.17	10.74	15.24	14.80	15.16
Different trials												
30 :	3.40	3.25	4.53	5.56	4.49	6.11	5.33	9.35	11.31	11.89	14.56	14.38
2 :	4.95	4.65	3.72	6.52	7.31	6.31	8.70	10.47	9.56	17.99	15.04	17.59
3 :	4.86	3.74	2.49	5.02	5.74	5.16	7.24	9.06	9.39	11.86	14.97	12.06
4 :	4.60	3.48	5.03	9.18	5.63	7.32	10.61	11.35	12.99	21.57	17.45	18.71
5 :	3.12	4.61	4.93	5.11	4.39	5.69	6.38	11.37	11.05	12.58	12.85	13.07
6 :	4.02	4.57	4.30	5.91	5.92	8.07	9.83	10.24	9.14	15.02	17.69	16.22
Subject 3												
Same trials												
30 :	5.87	4.17	5.05	6.14	6.72	6.05	7.64	7.70	8.98	10.80	8.80	9.38
2 :	4.58	4.50	4.98	5.88	6.46	6.44	10.61	11.96	10.70	14.75	14.94	14.83
3 :	3.40	3.48	3.49	5.58	6.51	6.02	11.47	7.59	7.68	12.21	11.62	10.44
4 :	2.91	3.44	3.98	3.67	4.77	6.03	6.83	7.98	8.25	10.87	8.11	11.56
5 :	3.34	4.13	3.67	5.27	3.68	5.12	9.86	10.25	9.63	13.33	10.72	11.22
6 :	3.41	2.91	3.46	3.92	4.19	3.90	6.99	9.27	8.71	10.69	8.87	11.94
Different trials												
30 :	3.26	3.82	3.95	5.20	3.61	5.41	7.29	9.09	8.02	9.27	13.30	11.30
2 :	3.28	2.68	3.57	5.82	4.85	4.29	7.88	9.04	7.15	12.14	13.16	9.84
3 :	3.01	3.50	2.98	4.62	4.44	4.15	7.23	9.14	9.45	11.11	7.88	10.43

4 :	2.85	2.95	2.69	4.97	5.15	4.89	9.10	9.38	9.91	12.04	12.17	11.42
5 :	3.91	3.52	3.97	6.02	4.14	5.02	7.60	8.44	9.09	7.58	8.71	12.76
6 :	4.87	3.30	4.05	4.54	4.47	5.49	7.60	9.36	10.07	12.27	11.87	12.60

Same trials

Subject 4

30 :	3.16	3.25	3.47	4.71	4.16	3.82	7.17	5.40	6.53	6.48	6.68	7.70
2 :	3.15	3.41	3.76	4.31	4.15	4.36	6.22	6.18	7.53	9.34	8.42	8.33
3 :	3.11	3.68	4.03	3.54	4.58	3.91	6.98	8.88	7.05	13.04	8.17	9.92
4 :	4.06	2.95	3.14	3.30	5.14	3.73	8.43	8.25	6.59	10.93	9.45	8.85
5 :	3.49	4.05	3.94	4.78	7.07	6.90	7.17	8.39	6.96	10.33	11.86	9.71
6 :	3.16	3.35	2.68	3.83	4.14	5.60	6.67	7.49	7.66	9.59	8.49	9.89

Different trials

30 :	2.78	3.29	3.56	5.09	4.84	4.88	8.11	8.64	8.11	8.53	8.72	10.59
2 :	2.85	2.41	2.81	4.73	3.28	4.39	6.72	8.77	6.50	8.97	11.26	10.12
3 :	3.22	4.04	2.58	4.44	4.22	4.78	5.89	7.76	7.07	11.23	9.51	10.30
4 :	3.01	3.25	2.88	4.22	4.40	3.66	9.20	10.59	10.54	11.45	8.77	8.79
5 :	3.34	2.50	3.64	6.17	4.47	4.78	7.65	7.55	9.33	9.67	10.65	9.05
6 :	3.42	3.35	2.20	3.98	4.13	5.07	5.75	8.82	9.38	10.75	10.20	11.29

Subject 5

Same trials

30 :	6.60	5.05	6.67	8.12	6.76	6.33	8.10	6.92	8.03	9.80	8.68	8.90
2 :	9.79	7.24	7.33	10.26	8.22	8.32	12.95	9.77	12.12	11.76	13.70	10.90
3 :	2.59	2.96	2.05	3.57	4.39	3.75	6.74	6.21	6.09	5.85	7.95	9.52
4 :	2.73	2.85	1.56	2.80	3.71	3.16	6.22	6.77	5.54	7.79	6.10	5.71
5 :	2.79	2.70	3.29	3.23	5.10	3.16	7.33	7.54	5.70	7.14	8.00	7.43
6 :	3.41	2.00	1.91	3.22	3.32	3.73	5.14	5.13	6.42	6.38	6.40	7.13

Different trials

30 :	2.54	2.99	2.46	4.10	3.38	3.65	7.90	6.59	4.74	7.71	6.48	7.46
2 :	2.12	2.19	2.39	3.63	2.41	2.96	5.48	4.58	6.63	5.91	7.99	5.75
3 :	2.68	3.12	2.43	3.23	3.73	3.53	4.83	5.74	6.76	8.16	7.30	5.57
4 :	2.27	2.03	2.16	4.44	3.84	2.96	6.46	7.52	5.35	7.70	6.18	5.44
5 :	3.56	3.42	2.81	3.77	3.96	4.56	7.37	5.77	6.37	6.70	9.20	6.71
6 :	5.09	1.83	2.71	4.15	3.60	4.55	6.60	6.61	8.94	7.78	7.29	7.77

Subject 6

Same trials

30 :	4.78	4.96	4.37	6.64	5.46	6.27	8.24	6.25	6.80	9.66	8.26	11.51
2 :	4.98	4.35	6.27	5.69	5.13	4.92	6.83	6.46	8.71	9.77	8.46	12.08
3 :	3.02	4.10	3.76	3.66	4.74	4.82	8.38	7.21	6.52	9.39	8.58	7.70
4 :	4.23	3.09	3.74	4.88	4.15	4.08	5.10	5.35	7.22	9.60	6.28	8.00
5 :	3.88	3.45	4.62	3.54	5.04	4.42	7.33	4.98	6.56	8.48	8.33	7.65
6 :	4.13	3.43	3.82	3.60	4.69	3.57	6.23	8.18	5.88	9.07	8.23	9.36

Different trials

30 :	2.93	3.75	2.94	4.61	4.55	4.40	6.50	6.54	7.84	10.09	7.39	9.42
2 :	4.81	4.37	3.45	4.22	4.47	3.88	6.34	5.79	6.30	8.10	7.48	7.90
3 :	3.16	3.47	3.90	4.47	4.16	4.08	6.79	7.23	7.61	8.64	7.93	6.89
4 :	4.16	3.95	3.49	5.52	4.57	4.57	6.76	7.57	7.96	8.11	8.00	10.00
5 :	4.31	2.96	3.98	3.67	4.58	3.64	6.96	5.91	6.08	7.98	7.84	8.47
6 :	4.22	4.74	3.56	5.08	5.18	5.04	6.24	6.86	6.82	9.11	7.17	7.49

August 19, 1986

Addendum

We are currently studying performance on the structure comparison task with a single (stationary) view of each simulated object. Preliminary results indicate that above chance performance may be possible in this condition. These new results may alter the interpretations presented in this report.

Erratum


P. 20. The page numbers for Hoffman and Bennett, 1986, should be 71-83.

Studies in the Cognitive Sciences

1. Peter W. Culicover and Michael Rochemont, "Stress and Focus in English" (April 1981).
2. John I. Yellott, Jr., "Seeing Things Inside Out" (July 1981).
3. Peter W. Culicover, "Learnability Explanations and Processing Explanations" (June 1981).
4. Thomas R. Nelson, R. Jacob Leonesio, Arthur P. Shimamura, Robert F. Landwehr and Louis Narens, "Overlearning and the Feeling of Knowing" (July 1981).
5. Myron L. Braunstein, George J. Andersen, and David M. Riefer, "The Use of Occlusion to Resolve Ambiguity in Parallel Projections" (July 1981).
6. W. C. Watt, "Semiotic Systemhood" (August 1981).
7. Kenneth Ralph Stern, "Contour Angle and Linear Perspective Effects on the Perceived Direction of Rotary Motion" (September 1981).
8. V. S. Ramachandran and S. M. Anstis, "Extrapolation of Motion Path in Human Visual Perception" (September 1981).
9. Gerald Patrick Delahunty, "Topics in the Syntax and Semantics of English Cleft Sentences" (In four fascicles) (September 1981).
10. Lynn Nadel, "Cognitive Maps: At the Choice Point Again" (October 1981).
11. V. S. Ramachandran, "Perception of Apparent Movement" (October 1981).
12. Louis Narens and R. Duncan Luce, "How We May Have Been Misled Into Believing in the Interpersonal Comparability of Utility" (February 1982).
13. Robert M. Harnish, Four Lectures on Inferential Pragmatics (in two fascicles) (March 1982).
14. Adrienne Frostholm, William Bennett and Gary Lynch, "Behavioral Abnormalities of Murine Muscular Dystrophy" (April 1982).
15. A. Kimball Romney, "Systemic Culture Patterns and High Concordance Codes" (June 1982).

16. V. S. Ramachandran and S. M. Anstis, "Laws of Perceptual Organization in Multistable Apparent Motion" (November 1982).
17. Tarow Indow and Toshio Watanabe, "Parallel- and Distance-Alleys on Horopter Plane in the Dark" (November 1982).
18. Tarow Indow and Toshio Watanabe, "Parallel—and Distance—Alleys with Moving Points in the Horizontal plane" (November 1982).
19. W. C. Watt, "Signs of the Times" (February 1983).
20. Victorina D. Lefebvre, "Ethical features of the normative hero in Soviet children's literature of 1960s-70s" (February 1983).
21. R. Duncan Luce and Louis Narens, "Symmetry, Scale Types, and Generalizations of Classical Physical Measurement" (February 1983).
22. Lin Chen, "What Are the Units of Figure Perceptual Representation" (February 1983).
23. Rupert Pentweazle, "Architecture, Movies, Cattlebrands, and the Ineffable" (April 1983).
24. George J. Andersen and Myron L. Braunstein, "Induced Self-Motion in Central Vision" (September 1984).
25. A. Kimball Romney, Susan C. Weller, and William H. Batchelder, "Culture as Consensus: A Theory of Culture and Informant Accuracy" (October 1984).
26. W. C. Watt, "The Byblos Matrix" (October 1984).
27. Vladimir A. Lefebvre, "The Golden Section and an Algebraic Model of Ethical Cognition" (November 1984).
28. Tom N. Cornsweet and John I. Yellott, Jr., "Image Processing by Intensity Dependent Spatial Summation" (November 1984).
29. D. D. Hoffman and B. M. Bennett, "The Computation of Structure from Fixed Axis Motion: Rigid Structures" (November 1984).
30. William H. Batchelder and David M. Riefer, "The Statistical Analysis of a Model for Storage and Retrieval Processes in Human Memory" (March 1985).
31. W. C. Watt, "What is the Proper Characterization of the Alphabet? IV: Union" (March 1985).

32. Vladimir A. Lefebvre, "The Fundamental Structures of Human Reflexion" (March 1985).
33. Louis Narens and R. Duncan Luce, "Measurement: The Theory of Numerical Assignments" (April 1985).
34. Louis Narens and R. Duncan Luce, "Measurement, Theory Of" (June 1985).
35. D.D. Hoffman and B.M. Bennett, "Visual Representations: Meaning and Truth Conditions" (July 1985).
36. W. C. Watt, "Vestiges of a Ugaritian Phonological Matrix Embodied in the English Alphabet" (October 1985).
37. Vladimir A. Lefebvre, Victorina D. Lefebvre and Jack Adams-Webber, "Modeling an Experiment on Construing Self and Others" (January 1986).
38. W. C. Watt, "Canons of Alphabetic Change" (February 1986).
39. Hagit Borer and Kenneth Wexler, "The Maturation of Syntax" (March 1986).
40. W. C. Watt, "Sign and Signifex" (April 1986).
41. Myron L. Braunstein, Donald D. Hoffman, Lionel R. Shapiro, George J. Andersen and Bruce M. Bennett, "Minimum Points and Views for the Recovery of Three-Dimensional Structure" (July 1986).



January 1986

OFFICE OF NAVAL RESEARCH
Engineering Psychology Program
TECHNICAL REPORTS DISTRIBUTION LIST

OSD

CAPT Paul R. Chatelier
Office of the Deputy Under Secretary
of Defense
OUSDRE (E&LS)
Pentagon, Room 3D129
Washington, D. C. 20301

Department of the Navy
Engineering Psychology Program
Office of Naval Research
Code 1142EP
800 North Quincy Street
Arlington, VA 22217-5000 (3 copies)

Aviation & Aerospace Technology
Programs
Code 121
Office of Naval Research
800 North Quincy Street
Arlington, VA 22217-5000

Physiology and Neurobiology Program
Office of Naval Research
Code 1141NP
800 North Quincy Street
Arlington, VA 22217-5000

CAPT. P. M. Curran
Code 125
Office of Naval Research
800 North Quincy Street
Arlington, VA 22217-5000

Dr. Charles Holland
Office of Naval Research
Code 1133
800 N. Quincy Street
Arlington, VA 22217-5000

J. Randy Simpson
Statistics Program Code 1111SP
Office of Naval Research
800 North Quincy Street
Arlington, VA 22217-5000

Dr. Lyle D. Broemeling
Code 1111SP
Office of Naval Research
800 N. Quincy Street
Arlington, VA 22217-5000

Information Sciences Division
Code 1133
Office of Naval Research
800 North Quincy Street
Arlington, VA 22217-5000

CAPT William M. Houk
Commanding Officer
Naval Medical R&D Command
Bethesda, MD 20814-5055

Dr. Randall P. Schumaker
NRL A. I. Center
Code 7510ical R&D Command
Naval Research Laboratory
Washington, D.C. 20375-5000

JANUARY 1986

Department of the Navy

Special Assistant for Marine
Corps Matters
Code OOMC
Office of Naval Research
800 North Quincy Street
Arlington, VA 22217-5000

Mr. R. Lawson
ONR Detachment
1030 East Green Street
Pasadena, CA 91106-2485

CDR James Offutt
Office of the Secretary of Defense
Strategic Defense Initiative Organization
Washington, D.C. 20301-7100

Director
Technical Information Division
Code 2627
Naval Research Laboratory
Washington, D.C. 20375-5000

Dr. Michael Melich
Communications Sciences Division
Code 7500
Naval Research Laboratory
Washington, D.C. 23075-5000

Dr. J. S. Lawson, Jr.
4773-C Kahala Avenue
Honolulu, HI 96816

Dr. Neil McAlister
Office of Chief of Naval Operations
Command and Control
OP-094H
Washington, D. C. 20350

Dr. A. F. Norcio
Computer Sciences & Systems
Code 7592
Naval Research Laboratory
Washington, DC 20375-5000

Dr. James McMichael
Office of the Chief of Naval
Operations, OP987H
Technology Assessment Division
Washington, D. C. 20350

Mr. John Davis
Combat Control Systems Department
Code 35
Naval Underwater Systems Center
Newport, RI 02840

Human Factors Department
Code N-71
Naval Training Systems Center
Orlando, FL 32813

Mr. Norm Beck
Combat Control Systems Department
Code 35
Naval Underwater Systems Center
Newport, RI 02840

Human Factors Engineering
Code 441
Naval Ocean Systems Center
San Diego, CA 92152

Dr. Gary Poock
Operations Research Department
Naval Postgraduate School
Monterey, CA 93940

Mr. H. Talkington
Engineering & Computer Science
Code 09
Naval Ocean Systems Center
San Diego, CA 92152

CDR Paul Girard
Command & Control Technology
Department, Code 40
Naval Ocean Systems Center
San Diego, CA 92152

Department of the Navy

Mr. Paul Heckman
Naval Ocean Systems Center
San Diego, CA 92152

Dr. William Uttal
Naval Ocean Systems Center
Hawaii Laboratory
P. O. Box 997
Kailua, HI 96734

Dr. A. L. Slafkosky
Scientific Advisor
Commandant of the Marine Corps
Washington, D. C. 20380

Dr. L. Chmura
Computer Sciences & Systems
Code 7592
Naval Research Laboratory
Washington, D.C. 20375-5000

Dr. Michael Letsky
Office of the Chief of Naval
Operations (OP-01B7)
Washington, D.C. 20350

Professor Douglas E. Hunter
Defense Intelligence College
Washington, D.C. 20374

CDR C. Hutchins
Code 55
Naval Postgraduate School
Monterey, CA 93940

Dr. Stanley Collyer
Office of Naval Technology
Code 222
800 North Quincy Street
Arlington, VA 22217-5000

Professor Michael Sovereign
Joint Command, Control &
Communications Curriculum
Code 74
Naval Postgraduate School
Monterey, CA 93943

Commander
Naval Air Systems Command
Crew Station Design
NAVAIR 5313
Washington, D. C. 20361

Mr. Philip Andrews
Naval Sea Systems Command
NAVSEA 61R
Washington, D. C. 20362

Aircrew Systems Branch
Systems Engineering Test
Directorate
U.S. Naval Test Center
Patuxent River, MD 20670

Mr. Milton Essoglou
Naval Facilities Engineering
Command
R&D Plans and Programs
Code 03T
Hoffman Building II
Alexandria, VA 22332

CAPT Robert Biersner
Naval Biodynamics Laboratory
Michoud Station
Box 29407
New Orleans, LA 70189

Dr. Arthur Bachrach
Behavioral Sciences Department
Naval Medical Research Institute
Bethesda, MD

Dr. George Moeller
Human Factors Engineering Branch
Naval Submarine Base
Submarine Medical Research Lab.
Groton, CT 06340

JANUARY 1986

Department of the Navy

Head
Aerospace Psychology Department
Naval Aerospace Medical Research Lab
Pensacola, FL 32508

Commanding Officer
Naval Health Research Center
San Diego, CA 92152

Dr. Jerry Tobias
Auditory Research Branch
Submarine Medical Research Lab
Naval Submarine Base
Groton, CT 06340

Dr. Robert Blanchard
Code 71
Navy Personnel Research and
Development Center
San Diego, CA 92152-6800

LCDR T. Singer
Human Factors Engineering Division
Naval Air Development Center
Warminster, PA 18974

Mr. Jeff Grossman
Human Factors Division, Code 71
Navy Personnel R&D Center
San Diego, CA 92152-6800

LT. Dennis McBride
Human Factors Branch
Pacific Missile Test Center
Point Mugu, CA 93042

Dr. Kenneth L. Davis
Code 1114
Office of Naval Research
800 North Quincy Street
Arlington, VA 22217-5000

LCDR R. Carter
Office of Chief on Naval Operations
(OP-01B)
Washington, D.C. 20350

Dean of the Academic Departments
U. S. Naval Academy
Annapolis, MD 21402

CDR W. Moroney
Naval Air Development Center
Code 602
Warminster, PA 18974

Dr. Harry Crisp
Code N 51
Combat Systems Department
Naval Surface Weapons Center
Dahlgren, VA 22448

Mr. John Quirk
Naval Coastal Systems Laboratory
Code 712
Panama City, FL 32401

Human Factors Branch
Code 3152
Naval Weapons Center
China Lake, CA 93555

CDR Kent S. Hull
MS 239-21
NASA/Ames Research Center
Moffett Field, CA 94035

Dr. Rabinder N. Madan
Code 1114SE
Office of Naval Research
800 North Quincy Street
Arlington, VA 22217-5000

Dr. Eugene E. Glove
ONR Detachment
1030 East Green Street
Pasadena, CA 91106-2485

JANUARY 1986

Dr. Glen Allgaier
Artificial Intelligence Branch
Code 444
Naval Electronics Ocean System Center
San Diego, CA 921525

Dr. Steve Sacks
Naval Electronics Systems Command
Code 61R
Washington, D.C. 20363-5100

Dr. Sherman Gee
Command and Control Technology, (Code 221)
Office of Naval Technology,
800 N. Quincy Street
Arlington, VA 22217-5000

Dr. Robert A. Fleming
Human Factors Support Group
Naval Personnel Research & Development Ctr.
1411 South Fern Street
Arlington, VA 22202

Department of the Army

Dr. Edgar M. Johnson
Technical Director
U.S. Army Research Institute
Alexandria, VA 22333-5600

Technical Director
U.S. Army Human Engineering Laboratory
Aberdeen Proving Ground, MD 21005

Director, Organizations and Systems
Research Laboratory
U.S. Army Research Institute
5001 Eisenhower Avenue
Alexandria, VA 22333-5600

Dr. Milton S. Katz
Director, Basic Research
Army Research Institute
5001 Eisenhower Avenue
Alexandria, VA 22333-5600

Department of the Air Force

Dr. Kenneth R. Boff
AF AMRL/HE
Wright-Patterson AFB, OH 45433

Dr. A. Fregly
U.S. Air Force Office of
Scientific Research
Life Science Directorate, NL
Bolling Air Force Base
Washington, D.C. 20332-6448

Mr. Charles Bates, Director
Human Engineering Division
USAF AMRL/HES
Wright-Patterson AFB, OH 45433

Dr. Earl Alluist
Chief Scientist
AFHRL/CCN
Brooks Air Force Base, TX 78235

Dr. J. Tangney
Directorate Life Sciences
AFSOR
Bolling AFB
Washington, D.C. 20032-6448

Mr. Yale Smith
Rome Air Development
Center, RADC/COAD
Griffiss AFB
New York 13441-5700

Dr. A. D. Baddeley
Director, Applied Psychology
Unit
Medical Research Council
15 Chaucer Road
Cambridge, CB2 2EF England

Dr. Kenneth Gardner
Applied Psychology Unit
Admiralty Marine Tech. Estab.
Teddington, Middlesex
TW11 0LN
England

JANUARY 1986

Other Government Agencies

Dr. M. C. Montemerlo
Information Sciences &
Human Factors Code RC
NASA HQS
Washington, D.C. 20546

Dr. Alan Leshner
Deputy Division Director
Division of Behavioral and
Neural Sciences
National Science Foundation
1800 G. Street, N.W.
Washington, D.C. 20550

Defense Technical Information
Center
Cameron Station, Bldg. 5
Alexandria, VA 22314 (2 copies)

Dr. Clinton Kelly
Defense Advanced Research
Projects Agency
1400 Wilson Blvd.
Arlington, VA 22209

Other Organizations

Dr. Harry Snyder
Dept. of Industrial Engineering
Virginia Polytechnic Institute
and State University
Blacksburg, VA 24061

Dr. Amos Tversky
Dept. of Psychology
Stanford University
Stanford, CA 94305

Dr. Amos Freedy
Perceptrons, Inc.
6271 Variel Avenue
Woodland Hills, CA 91364

Dr. Jesse Orlansky
Institute for Defense Analyses
1801 N. Beauregard Street
Alexandria, VA 22311

Dr. Donald D. Hoffman
University of California
(Irvine)
School of Social Sciences
Irvine, CA 92717

Dr. T. B. Sheridan
Dept. of Mechanical
Engineering
Massachusetts Institute of
Technology
Cambridge, MA 02139

Dr. Daniel Kahneman
The University of British
Columbia
Department of Psychology
#154-2053 Main Mall
Vancouver, British Columbia
Canada V6T 1Y7

Dr. Stanley Deutsch
NAS-National Research Council
(COHF)
2101 Constitution Avenue, N.W.
Washington, D.C. 20418

Dr. Meredith P. Crawford
American Psychological
Association
Office of Educational Affairs
1200 17th Street N.W.
Washington, D.C. 20036

Dr. Deborah Boehm-Davis
Department of Psychology
George Mason University
4400 University Drive
Fairfax, VA 22030

Other Organizations

Dr. David Van Essen
California Institute of Tech.
Division of Biology
Pasadena, CA 91125

Dr. James H. Howard, Jr.
Department of Psychology
Catholic University
Washington, D.C. 20064

Dr. William Howell
Department of Psychology
Rice University
Houston, TX 77001

Dr. Christopher Wickens
Department of Psychology
University of Illinois
Urbana, IL 61801

Dr. Robert Wherry
Analytics, Inc.
2500 Maryland Road
Willow Grove, PA 19090

Dr. Edward R. Jones
Chief, Human Factors Engineering
McDonnell-Douglas Astronautics Co.
St. Louis Division
Box 516
St. Louis, MO 63166

Dr. Lola L. Lopes
Department of Psychology
University of Wisconsin
Madison, WI 53706

Dr. Joaquin Fuster
University of California at
Los Angeles
760 Westwood Plaza
Los Angeles, CA 90024

Dr. Stanley N. Roscoe
New Mexico State University
Box 5095
Las Cruces, NM 88003

Mr. Joseph G. Wohl
Alphatech, Inc.
3 New England Executive Park
Burlington, MA 10803

Dr. Marvin Cohen
Decision Science Consortium, Inc.
Suite 721
7700 Leesburg Pike
Falls Church, VA 22043

Dr. Scott Robertson
Catholic University
Department of Psychology
Washington, D.C. 20064

Dr. William B. Rouse
School of Industrial and Systems
Engineering
Georgia Institute of Technology
Atlanta, GA 30332

Ms. Denise Benel
Essex Corporation
333 N. Fairfax Street
Alexandria, VA 22314

Dr. Andrew P. Sage
Assoc. V. P. for Academic Affairs
George Mason University
4400 University Drive
Fairfax, VA 22030

Dr. James Ballas
Georgetown University
Department of Psychology
Washington, D.C. 20057

Other Organizations

Dr. Richard Pew
Bolt Beranek & Newman, Inc.
50 Moulton Street
Cambridge, MA 02238

Dr. Hillel Einhorn
Graduate School of Business
University of Chicago
1101 E. 58th Street
Chicago, IL 60637

Dr. Douglas Towne
University of Southern California
Behavioral Technology Lab
1845 South Elena Avenue, Fourth Floor
Redondo Beach, CA 90277

Dr. James T. Todd
Brandeis University
Waltham, MA 02254

Dr. John Payne
Graduate School of Business
Administration
Duke University
Durham, NC 27706

Dr. Dana Yoerger
Deep Submergence Laboratory
Woods Hole Oceanographic
Institution
Woods Hole, MA 02543

Dr. Azad Madni
Perceptronic, Inc.
6271 Varie! Avenue
Woodland Hills, CA 91364

Dr. Tomaso Poggio
Massachusetts Institute of Tech.
Center for Biological Information
Processing
Cambridge, MA 02139

Dr. Whitman Richards
Massachusetts Ins. of Tech
Department of Psychology
Cambridge, MA 02139

Dr. Robert A. Hummel
New York University
Courant Inst. of Mathematical
Sciences
251 Mercer Street
New York, New York 10012

Dr. H. McI. Parsons
Essex Corporation
333 N. Fairfax Street
Alexandria, VA 22314

Dr. Paul Slovic
Decision Research
1201 Oak Street
Eugene, OR 97401

Dr. Kent A. Stevens
University of Oregon
Dept. of Computer & Info Sci.
Eugene, OR 97403

Dr. Donald A. Glaser
U. of California, Berkeley
Department of Molecular Biology
Berkeley, CA 94720

Other Organizations

Dr. Leonard Adelman
PAR Technology Corp.
Building A
1220 Sunset Hills Road, Suite 310
McLean, VA 22090

Dr. Michael Athans
Massachusetts Inst. of Technology
Lab Information & Decision Systems
Cambridge, MA 02139

Dr. David Castanon
ALPHATECH, Inc.
111 Middlesex Turnpike
Burlington, MA 01803

Dr. A. Ephremides
University of Maryland
Electrical Engineering Dept.
College Park, MD 20742

Dr. Baruch Fischhoff
Perceptronics, Inc.
6271 Variel Ave.
Woodland Hills, CA 91367

Dr. Bruce Hamill
The Johns Hopkins Univ.
Applied Physics Lab
Laurel, MD 20707

Barry Hughes
Space and Naval Warfare Systems
Code 611
Washington, D.C. 20363-5100

Dr. E. Douglas Jensen
Carnegie-Mellon University
Computer Science Dept.
Pittsburgh, PA 15213

Dr. David L. Kleinman
Electrical Engineering &
Computer Science Dept.
University of Connecticut
Storrs, CT 06268

Dr. Alexander Levis
Massachusetts Institute of
Technology
Lab Information & Decision Systems
Cambridge, MA 02139

Dr. D. McGregor
Perceptronics Inc.
1201 Oak Street
Eugene, OR 97401

Dr. David Noble
Engineering Research Assoc.
8616 Westwood Center Dr.
McLean, VA 22180

Dr. P. Papantoni-Kazakos
University of Connecticut
Department of Electrical Engin.
and Computer Science (U-157)
Storrs, CT 06268

Professor Wayne F. Stark
University of Michigan
Department of Electrical Eng.
and Computer Science
Ann Arbor, MI 48109

Mr. Robert L. Stewart
The Johns Hopkins University
Applied Physics Laboratory
Laurel, MD 20707

Dr. Kepi Wu
Space and Naval Warfare Systems
Code 611
Washington, D.C. 20363-5100

END

DTIC

9-86